# **AX338**

# long range rifle



# Specification

Calibre	0.338 Lapua Magnum (CIP)
Weight*	7.8kg (17.6lb)
Overall Length	1250mm (49.2")
Action	One-piece, machined from high grade steel
Trigger	Two-stage adjustable, set at 1.5-2.0kg (3.3-4.4lbs) Adjustable trigger shoe option
Safety Lever	Three position safety: 1st position blocks the firing pin and locks the bolt; 2nd (mid) position blocks the firing pin, but allows the bolt to be removed; 3rd (forward) position allows the weapon to be fired
Barrel	686mm (27") stainless steel match grade. Various twist rates available to suit specific ammunition types. Fitted with a high efficiency muzzle brake. Tactical muzzle brake and suppressor option available
Chassis	Adjustable cheekpiece, rear support leg, sling loops, moveable forward accessory rails and sight rail extensions to MIL-STD 1913
Rear Support Leg	Height adjustable design featuring both quick and fine adjustment.
Magazine	New detachable box type containing ten rounds
Carriage	Four sling attachment points – two adjustable forward mounts

<sup>\*</sup>including empty magazine, Q/A Cheekpiece, Q/A Butt, minus telescopic sight






# AX338

long range rifle

The highly advanced, new generation AX338 bolt action sniper rifle from Accuracy International is based on the DNA of the battle proven AW series. Inheriting the toughness, reliability, superb accuracy and ease of maintenance of it's celebrated predecessor, the AX Magnum action retains the same flat-bottom design, but is both longer (CIP/ SAAMI), and wider allowing the use of a compact and reliable double stack 10-round magazine. Simply perfection.





1 Butt pad

Fitted with either a bolt-on pad with 10mm and 20mm spacers or the optional quick-adjust butt pad the user can easily customise the length of pull. Butt pad height adjustment can be provided as an additional option

## 2 Adjustable Cheekpiece

The standard adjustable cheekpiece adjusts left/ right as well as for height to obtain optimum cheek position when using night vision equipment or telescopic sights with large objective lenses. The quick adjust cheek piece option offers a spring loaded platform for rapid tool-less adjustment.

This option allows the stock to be folded for transportation, reducing overall length by 9.25" (235mm) and adding 0.4lb (0.2kg). The stock locks positively in the folded position for security and the avoidance of noise. In the extended position, builtin wear compensation ensures total rigidity.

# 3 Folding chassis 4 Picatinny rail

reauest.

Fitted as standard, this rail provides an internationally accepted interface for many optical systems. Alternative height/angle options can be fitted on

# 5 Sling points

Two sling attachment

points are mounted on

each side as standard.

The two forward sling

points can be moved

according to user

preference.

The reliable, battle proven two stage mechanism from the AW series has a new trigger shoe for fore and aft adjustment up to 0.5" (13mm). Pull weights are adjustable from 3.3-4.4lb (1.5-2.0kg). The complete trigger assembly can easily be removed for cleaning by extracting two socket head cap screws.

assembly

6 Trigger

# 7 Barrel

The 27" match grade free floating barrel is threaded deep into the action with a large diameter thread unique to the AX338. Optional barrel lengths, twists, and calibres are available.

# 8 Butt spike

The extendable spike enables the user to observe the target area for extended periods with minimal fatigue. Designed with quick and fine adjustment to a maximum extended length of 115mm (4.5").

Standard features

Options

# 9 New stock

The new external stock design greatly improves the user's ability to carry and move with the rifle. A shorter rear stock makes shooting easier in bulky body armour. Available in either thumbhole or the new pistol grip configurations

# 10 Pistol grip

The ergonomically advanced pistol grip can be fine tuned to fit virtually any user by fitting one of several replaceable backstraps. The pistol grip, combined with the adjustable trigger shoe, allows the AX to achieve a fit like a target rifle. The traditional thumbhole stock is available as an option.

The larger new 0.87" (22mm) dia. steel close fitting bolt, bolt head, locking ring and barrel tenon construction is significantly stronger and capable of withstanding higher temperatures and pressures. An improved leaf-spring style extractor facilitates straightforward removal and replacement.

11 Modular bolt

be maintained.

## 12 Bonded action

A new strengthened design ensures safety in the most extreme environments. It is permanently bonded and bolted to the stiff aluminium chassis to eliminate movement, ensuring that zero will

# 13 Magazine

Surface toughened. and finished with a multi-part anti-corrosive, anti-friction coating. the compact 10-round double row, military grade steel magazine combined with the revised chassis design makes loading faster and more positive without lifting the rifle.

# 14 Forend rail

system

Free floating tube forend features a slot system for quickly, and securely attaching modular rail sections allowing the user to fit a virtually unlimited variety of optical, ranging, support and carrying accessories.

Accuracy

All rifles are shot and function tested before leaving the factory.