

AX50

anti matériel rifle

Designed to withstand constant military deployment, the new generation AX50 long range anti matérial rifle from Accuracy International is based on the DNA of the battle proven AW50. Inheriting the toughness, reliability and ease of maintenance of it's powerful predecessor, the AX50 exhibits all the features necessary to ensure superb accuracy and consistent cold shot performance in the harshest conditions. Simply perfection.



Butt pad

The AX50 is fitted with a large, recoil absorbing, butt pad for increased comfort. The user can easily customise the length of pull using the 10mm butt spacers included.

2 Adjustable Cheekpiece

A height adjustable, cheekpiece is fitted as standard and allows the user to obtain an optimum cheek position when using night vision equipment or telescopic sights with large objective lenses.

The extendable rear to observe the target area for extended periods with minimal fatigue. Designed with quick and fine adjustment to a maximum extended

3 Rear observation support

support enables the user length of 50mm (2").

4 New stock design

The new external stock design facilitates a secure yet comfortable shooting position and greatly improves the user's ability to carry and move with the rifle. The polymer stock sides are impervious to all normal cleaners and lubricants used in small arms maintenance.

5 Folding chassis 6 Sling points

The chassis features a wear compensated hinge so the stock can be folded for parachute insertions or to facilitate transportation. The stock locks in the folded position for security and the avoidance of noise. and is easily released by pulling firmly on the butt. When folded, the overall length is reduced by 254mm (10").

Three sling attachment points are provided as standard. The two forward sling points can be moved according to user preference.

(4) (5)

Pistol grip

The ergonomically advanced pistol grip.

8 Action

A proprietary, flat

bottomed, high grade steel action is bolted to the full-length aluminium chassis. A full width recoil lug totally eliminates movement, ensuring that zero will be maintained in arduous conditions. Two pressure release points minimise blowback in the event of a cartridge failure. The integral Picatinny Rail provides an internationally accepted interface for many optical systems.

9 Trigger

The two-stage trigger allows a large sear engagement to be maintained until the first stage is taken up, thereby reducing the risk of an accidental discharge. Adjustable for pull weights of 1.5-2.0kg (3.3-4.4lb), the trigger can easily be removed for cleaning by simply loosening two socket-head screws.

assembly

cocked.

10 Safety mechanism

The 30mm diameter The two-position safety steel, close fitting bolt, combined with blocks the firing pin and locks the bolt in the closed vents and a gas shroud position when to the rear, minimises blowback in and allows the weapon to the event of a cartridge fire in the forward position. failure. The short-throw The safety will only (60°) handle lies close to operate when the bolt is the stock side, just above the trigger, to minimise movement of the user's hand.

11 Bolt

with a large, 39mm diameter thread, the rigidly mounted 27" match grade free floating barrel delivers consistent coldshot performance. The double chamber muzzle brake, screwed on and tension clamped, effectively reduces recoil, muzzle flash and dust eruption. A barrel can be changed in less than ten minutes using

12 Barrel

13 Magazine

feeding.

Screwed into the action the barrel change kit.

14 Forend rail system

One five-shot detachable Free floating tube forend steel magazine is included. This industry featuring a keyhole leading design is slot system for quickly corrosion resistant and and securely attaching low friction for reliable modular rail sections allowing the user to fit a virtually unlimited variety of optical, ranging, support and carry options.

Accuracy

All rifles are shot and function tested before leaving the factory.

AX50

anti matériel rifle



Specification

Calibre	0.50 cal BMG (12.7 x 99mm)		
Weight*	12.5kg (27.5lb)		
Overall length	1370mm (53.9") extended, 1115mm (43.9") folded		
Action	One-piece, machined from high grade steel		
Trigger	Two-stage adjustable, set at 1.5-2.0kg (3.3-4.4lbs)		
Safety lever	Two positon safety lever ('Safe' and 'Fire')		
Barrel	692mm (27") free floating, stainless steel match grade. 1 in 15" twist. Fitted with a high efficiency muzzle brake		
Chassis	Folding chassis with adjustable cheekpiece, moveable forward sling loops, accessory rails and sight rail extensions to MIL STD 1913		
Rear Observation support	Height adjustable design featuring both quick and fine adjustment		
Magazine	Detachable box type containing five rounds		
Carriage	Three sling attachment points (two adjustable forward mounts)		
Stockside colour**	BLACK		DARK EARTH

^{*}minus scope, empty magazine **Barrels and actions are black





www.accuracyinternational.com

Accuracy International reserves the right to change specifications without notice.